FEniCS Course

Lecture 9: Incompressible Navier–Stokes

Contributors
Anders Logg



The incompressible Navier–Stokes equations

$$\begin{split} \rho(\dot{u} + u \cdot \nabla u) - \nabla \cdot \sigma(u, p) &= f &\quad \text{in } \Omega \times (0, T] \\ \nabla \cdot u &= 0 &\quad \text{in } \Omega \times (0, T] \\ u &= g_{\text{D}} &\quad \text{on } \Gamma_{\text{D}} \times (0, T] \\ \sigma \cdot n &= g_{\text{N}} &\quad \text{on } \Gamma_{\text{N}} \times (0, T] \\ u(\cdot, 0) &= u_0 &\quad \text{in } \Omega \end{split}$$

- \bullet u is the fluid velocity and p is the pressure
- ρ is the fluid density
- $\sigma(u,p) = 2\mu\epsilon(u) pI$ is the Cauchy stress tensor
- $\epsilon(u) = \frac{1}{2}(\nabla u + (\nabla u)^{\top})$ is the symmetric gradient
- f is a given body force per unit volume
- $g_{\rm D}$ is a given boundary displacement
- g_N is a given boundary traction
- u_0 is a given initial velocity

Variational problem

Multiply the momentum equation by a test function v and integrate by parts:

$$\int_{\Omega} \rho(\dot{u} + u \cdot \nabla u) \cdot v \, \mathrm{d}x + \int_{\Omega} \sigma(u, p) : \epsilon(v) \, \mathrm{d}x = \int_{\Omega} f \cdot v \, \mathrm{d}x + \int_{\Gamma_{\mathrm{N}}} g_{\mathrm{N}} \cdot v \, \mathrm{d}s$$

Short-hand notation:

$$\langle \rho \dot{u}, v \rangle + \langle \rho u \cdot \nabla u, v \rangle + \langle \sigma(u, p), \epsilon(v) \rangle = \langle f, v \rangle + \langle g_{\text{\tiny N}}, v \rangle_{\Gamma_{\text{\tiny N}}}$$

Multiply the continuity equation by a test function q and sum up: find $(u, p) \in V$ such that

$$\langle \rho \dot{u}, v \rangle + \langle \rho u \cdot \nabla u, v \rangle + \langle \sigma(u, p), \epsilon(v) \rangle + \langle \nabla \cdot u, q \rangle = \langle f, v \rangle + \langle g_{\text{\tiny N}}, v \rangle_{\Gamma_{\text{\tiny N}}}$$

for all $(v,q) \in \hat{V}$

Discrete variational problem

Time-discretization leads to a *saddle-point* problem on each time step:

$$\left[\begin{array}{cc} M + \Delta t A + \Delta t N(U) & \Delta t B \\ \Delta t B^{\top} & 0 \end{array}\right] \left[\begin{array}{c} U \\ P \end{array}\right] = \left[\begin{array}{c} b \\ 0 \end{array}\right]$$

- Efficient solution of the saddle-point problem relies on the efficiency of special-purpose preconditioners (Uzawa iteration, Schur complement preconditioners, ...)
- We will use another approach (simpler and often more efficient)

A splitting method

cG(1) / Crank-Nicolson approximation with explicit convection:

$$\rho D_t u^n + \rho u^{n-1} \cdot \nabla u^{n-1} - \nabla \cdot \sigma(u^{n-1/2}, p^{n-1/2}) = f^{n-1/2}$$

Compute the tentative velocity u^* using the approximation

$$\rho D_t u^{\bigstar} + \rho u^{n-1} \cdot \nabla u^{n-1} - \nabla \cdot \sigma(u^{n-1/2}, p^{n-3/2}) = f^{n-1/2}$$

Subtract:

$$\rho(D_t u^n - D_t u^{\bigstar}) - \nabla \cdot \sigma(0, p^{n-1/2} - p^{n-3/2}) = 0$$

Expand and rearrange:

$$\rho(u^n - u^{\bigstar}) + k_n \nabla (p^{n-1/2} - p^{n-3/2}) = 0$$

$$D_t u = (u^n - u^{n-1})/k_n$$
 and $k_n = t_n - t_{n-1}$

A splitting method (contd.)

We have found that:

$$\rho(u^n - u^{\bigstar}) + k_n \nabla(p^{n-1/2} - p^{n-3/2}) = 0$$

It follows that

$$\rho u^n = \rho u^{-1/2} - k_n \nabla (p^{n-1/2} - p^{n-3/2})$$
 (1)

Take the divergence and set $\nabla \cdot u^n = 0$:

$$-k_n \Delta p^{n-1/2} = -k_n \Delta p^{n-3/2} - \rho \nabla \cdot u^{\bigstar}$$
 (2)

- Compute $p^{n-1/2}$ by solving the Poisson problem (2)
- Compute u^n by solving the projection problem (1)
- To consider: What about the boundary conditions for the Poisson problem (2)?

Boundary conditions

• For outflow boundary conditions, corresponding to so-called "do-nothing" boundary conditions for the Laplacian formulation, we take $\partial_n u = 0$:

$$\sigma(u, p) \cdot n = (2\mu\epsilon(u) - pI) \cdot n = \mu \nabla u \cdot n + \mu(\nabla u)^{\top} \cdot n - pn$$
$$= \mu \nabla u \cdot n - pn \approx \mu \nabla u^{n-1/2} \cdot n - p^{n-3/2}n$$

• Boundary conditions for the pressure Poisson problem:

$$\partial_n \dot{p} = 0$$

on the pressure Neumann boundary

Incremental pressure correction scheme (IPCS)

1 Compute the tentative velocity u^* by

$$\langle \rho D_t^n u^{\bigstar}, v \rangle + \langle \rho u^{n-1} \cdot \nabla u^{n-1}, v \rangle + \langle \sigma(u^{n-\frac{1}{2}}, p^{n-3/2}), \epsilon(v) \rangle$$
$$- \langle \mu \nabla u^{n-\frac{1}{2}} \cdot n, v \rangle_{\partial \Omega} + \langle p^{n-3/2} n, v \rangle_{\partial \Omega} = \langle f^{n-1/2}, v \rangle$$

2 Compute the corrected pressure $p^{n-1/2}$ by

$$k_n \langle \nabla p^{n-1/2}, \nabla q \rangle = k_n \langle \nabla p^{n-3/2}, \nabla q \rangle - \langle \rho \nabla \cdot u^{\bigstar}, q \rangle$$

3 Compute the corrected velocity u^n by

$$\langle \rho u^n, v \rangle = \langle \rho u^{\bigstar}, v \rangle - k_n \langle \nabla (p^{n-1/2} - p^{n-3/2}), v \rangle$$

Useful FEniCS tools (I)

Note grad vs. ∇ :

```
dot(grad(u), u)
dot(u, nabla_grad(u))
```

Defining operators:

```
def sigma(u, p):
    return 2.0*mu*sym(grad(u)) - p*Identity(2)
```

The facet normal n:

```
n = FacetNormal(mesh)
```

Useful FEniCS tools (II)

Assembling matrices and vectors:

```
A = assemble(a)
b = assemble(L)
```

Solving linear systems:


```
solve(A, x, b)
solve(A, x, b, "gmres", "ilu")
solve(A, x, b, "cg", "amg")
```

Extracting left- and right-hand sides:

```
F = <complicated expression>
a = lhs(F)
L = rhs(F)
```

The FEniCS challenge!

Solve the incompressible Navier–Stokes equations for the flow of water around a dolphin. The water is initially at rest and the flow is driven by a pressure gradient.



The FEniCS challenge!

- Use the mesh dolfin_channel.xml.
- Compute the solution on the time interval [0, 0.1] with time steps of size k = 0.0005
- Set p = 1 kPa at the inflow and p = 0 at the outflow
- The density of water is $\rho=1000~{\rm kg/m^3}$ and the viscosity is $\mu=0.001002~{\rm kg/(m\cdot s)}$
- To check your answer, compute the average velocity in the x-direction.

The student(s) who first produce the right anwswer will be rewarded with an exclusive FEniCS surprise!