

Puffin User Manual

November 17, 2003



Anders Logg

This manual is written by:
Anders Logg.

Contents

1	Introduction	4
2	Mesh format	5
3	Specifying the variational formulation	6
4	The function <code>AssembleMatrix()</code>	8
5	The function <code>AssembleVector()</code>	9
6	Example programs	10
6.1	The program <code>PoissonSolver</code>	10
6.2	The program <code>ConvDiffStationarySolver</code>	10
6.3	The program <code>ConvDiffTimeDepSolver</code>	10

1 Introduction

This is a first draft for a Puffin manual. Contributions are most welcome.

Puffin is a simple and minimal implementation of FEniCS for Octave (MATLAB). It is based around the two functions `AssembleMatrix()` and `AssembleVector()`, which are used to assemble a linear system

$$AU = b, \tag{1}$$

representing a variational formulation of a differential equation,

$$a(u, v; w) = l(v; w) \quad \forall v \in V, \tag{2}$$

where $a(u, v; w)$ is a bilinear form in u (the trial function) and v (the test function), and $l(v; w)$ is a linear form in v . The bilinear form a and the linear form l are allowed to depend on a vector w (the coefficients), and are referred to as the left-hand side and the right-hand side of the variational formulation.

2 Mesh format

The mesh is assumed to be given by the three matrices `points`, `edges`, and `triangles`, representing the *points*, *edges*, and *triangles* of an unstructured triangular mesh in the plane.

FIXME: Add detailed description of the format.

3 Specifying the variational formulation

A variational formulation is given as a function in the following way:

```
function integral = MyForm(u, v, du, dv, dx, ds, x, d, w, t, eq)

if eq == 1
    integral = ... * dx + ... * ds;
else
    integral = ... * dx + ... * ds;
end
```

The output argument `integral` should be the integral of the left-hand or right-hand side (depending on the value of `eq`) of the variational formulation over a triangle (with area `dx`) or an edge (with length `ds`).

The input arguments are given by

- `u`: the value of the trial function u ,
- `v`: the value of the test function v ,
- `du`: the gradient ∇u of the trial function u ,
- `dv`: the gradient ∇v of the test function v ,
- `dx`: the area of the current triangle (zero if we are on an edge),
- `ds`: the length of the current edge (zero if we are on a triangle),
- `x`: the current quadrature point,
- `d`: the current domain number or edge number,
- `w`: a vector of coefficient values (optional),
- `t`: the value of time,

- `eq`: specifies left-hand side (1) or right-hand side (2) of the variational formulation.

As an example, consider the specification of the variational formulation for Poisson's equation. The variational formulation in mathematical notation is given by

$$\int_{\Omega} \nabla u \cdot \nabla v \, dx + \int_{\Gamma} \gamma uv \, ds = \int_{\Omega} f v \, dx + \int_{\Gamma} (\gamma g_D - g_N) v \, ds \quad \forall v. \quad (3)$$

For a certain choice of a , f , γ , g_D , and g_N , this can be specified by a function `Poisson()` as follows.

```
function integral = Poisson(u, v, du, dv, dx, ds, x, d, w, t, eq)

if eq == 1
    integral = du'*dv*dx + g(x,d,t)*u*v*ds;
else
    integral = f(x,d,t)*v*dx + (g(x,d,t)*gd(x,d,t) - gn(x,d,t))*v*ds;
end

%--- Conductivity (penalty factor) ---
function y = g(x, d, t)
y = 1e7;

%--- Dirichlet boundary condition ----
function y = gd(x, d, t)
y = 0;

%--- Neumann boundary condition ---
function y = gn(x, d, t)
y = 0;

%--- Right-hand side, source term ---
function y = f(x, d, t)
y = 5*pi^2*sin(pi*x(1))*sin(2*pi*x(2));
```

4 The function `AssembleMatrix()`

The syntax of the function `AssembleMatrix()` is

```
A = AssembleMatrix(points, edges, triangles, pde, W, time),
```

where the output argument is **A**, the matrix to be assembled, and the input arguments are given by

- **points**: the matrix containing the node coordinates of the mesh,
- **edges**: the matrix containing the edges of the mesh,
- **triangles**: the matrix containing the triangles of the mesh,
- **pde**: the name of the function specifying the variational formulation,
- **W**: a matrix where each column contains the nodal values of additional functions (coefficients) appearing in the variational formulation as the functions `w(1)`, `w(2)` and so on (leave empty (`[]`) if not needed),
- **time**: the value of time (the variable `t` in the variational formulation).

5 The function AssembleVector()

The syntax of the function `AssembleVector()` is

```
b = AssembleVector(points, edges, triangles, pde, W, time),
```

where the output argument is `b`, the vector to be assembled, and the input arguments are given by

- `points`: the matrix containing the node coordinates of the mesh,
- `edges`: the matrix containing the edges of the mesh,
- `triangles`: the matrix containing the triangles of the mesh,
- `pde`: the name of the function specifying the variational formulation,
- `W`: a matrix where each column contains the nodal values of additional functions (coefficients) appearing in the variational formulation as the functions `w(1)`, `w(2)` and so on (leave empty (`[]`) if not needed),
- `time`: the value of time (the variable `t` in the variational formulation).

6 Example programs

6.1 The program `PoissonSolver`

The program `PoissonSolver` solves Poisson's equation on the unit square, using the variational formulation specified by the function `Poisson()`.

6.2 The program `ConvDiffStationarySolver`

The program `ConvDiffStationarySolver` solves the stationary convection-diffusion equation around a cylinder, using the variational formulation specified by the function `ConvDiffStationary()`.

6.3 The program `ConvDiffTimeDepSolver`

The program `ConvDiffTimeDepSolver` solves the time-dependent convection-diffusion equation on the unit square, using the variational formulation specified by the function `ConvDiffTimeDep()`.